

ISO Nr.: 08B*

Passo / Pitch / Pas: 12.70 mm

Ø Rullo / Roller / Rouleau: 8.51 mm

Spessore pignone (mozzo escluso) / Sprocket thickness (hub excluded) /

Épaisseur du pignon (moyeu exclu): 7.2 mm

Dentature	Codice	Ø Foro (mm)	Spessore (mm) (mozzo incluso)	Ø esterno (mm)	Ø primitivo (mm)
Toothing	Code	Ø Hole (mm)	Thickness (mm) (hub included)	Ø external (mm)	Ø primitive (mm)
Dentures	Code	Ø Trou (mm)	Épaisseur (mm) (moyeu inclus)	Ø extérieur (mm)	Ø primitif (mm)
Z=10	PAZ1008B1	10	25	46.0	41.10
Z=11	PAZ1108B1	10	25	49.0	45.10
Z=12	PAZ1208B1	10	28	53.0	49.10
Z=13	PAZ1308B1	10	28	58.0	53.60
Z=14	PAZ1408B1	10	28	62.0	57.70
Z=15	PAZ1508B1	10	28	66.0	61.10
Z=16	PAZ1608B1	12	28	70.0	65.10
Z=17	PAZ1708B1	12	28	74.0	69.10
Z=18	PAZ1808B1	12	28	78.0	73.10
Z=19	PAZ1908B1	12	28	82.0	77.20
Z=20	PAZ2008B1	12	28	86.0	81.20
Z=21	PAZ2108B1	14	28	90.0	85.20
Z=22	PAZ2208B1	14	28	94.0	89.20
Z=23	PAZ2308B1	14	28	99.0	93.30
Z=24	PAZ2408B1	14	28	102.0	97.30
Z=25	PAZ2508B1	14	28	106.0	101.30
Z=26	PAZ2608B1	16	30	110.0	105.40
Z=27	PAZ2708B1	16	30	115.0	109.40
Z=28	PAZ2808B1	16	30	118.0	113.40
Z=29	PAZ2908B1	16	30	122.0	117.40
Z=30	PAZ3008B1	16	30	127.0	121.50
Z=31	PAZ3108B1	16	30	130.2	125.54
Z=32	PAZ3208B1	16	30	135.0	129.60
Z=33	PAZ3308B1	16	30	138.4	133.60
Z=34	PAZ3408B1	16	30	143.0	137.60
Z=35	PAZ3508B1	16	30	147.0	141.70
Z=36	PAZ3608B1	16	35	151.0	145.70
Z=37	PAZ3708B1	16	35	154.6	149.76
Z=38	PAZ3808B1	16	35	159.0	153.80
Z=39	PAZ3908B1	16	35	163.0	157.80
Z=40	PAZ4008B1	16	35	167.0	161.90

*Disponibile anche speciale a disegno e/o secondo normative ANSI/ASA. Disponibili nella versione semplice, doppia e tripla.

*Available also special at design and/or in conformity with ANSI/ASA regulations. Available in single, doubles and triple version.

*Disponibile aussi spécial au dessin et/ou selon normatives ANSI/ASA. Disponible la version simple, double et triple.