

**ISO Nr.: 12B\***

**Passo / Pitch / Pas: 19.05 mm**

**Ø Rullo / Roller / Rouleau: 12.07 mm**

**Spessore pignone (mozzo escluso) / Sprocket thickness (hub excluded) /**

**Épaisseur du pignon (moyeu exclu): 11.1 mm**

Dentature	Codice	Ø Foro (mm)	Spessore (mm) (mozzo incluso)	Ø esterno (mm)	Ø primitivo (mm)
Toothing	Code	Ø Hole (mm)	Thickness (mm) (hub included)	Ø external (mm)	Ø primitive (mm)
Dentures	Code	Ø Trou (mm)	Épaisseur (mm) (moyeu inclus)	Ø extérieur (mm)	Ø primitif (mm)
Z=10	PAZ1012B1	12	30	69.0	61.60
Z=11	PAZ1112B1	14	35	75.0	67.60
Z=12	PAZ1212B1	14	35	82.0	73.60
Z=13	PAZ1312B1	14	35	88.0	79.60
Z=14	PAZ1412B1	14	35	94.0	85.60
Z=15	PAZ1512B1	14	35	100.0	91.60
Z=16	PAZ1612B1	16	35	105.0	97.60
Z=17	PAZ1712B1	16	35	112.0	103.70
Z=18	PAZ1812B1	16	35	118.0	109.70
Z=19	PAZ1912B1	16	35	124.0	115.70
Z=20	PAZ2012B1	16	35	130.0	121.80
Z=21	PAZ2112B1	20	40	136.0	127.80
Z=22	PAZ2212B1	20	40	142.0	133.90
Z=23	PAZ2312B1	20	40	149.0	139.90
Z=24	PAZ2412B1	20	40	154.0	145.90
Z=25	PAZ2512B1	20	40	160.0	152.00
Z=26	PAZ2612B1	20	40	166.0	158.00
Z=27	PAZ2712B1	20	40	173.0	164.10
Z=28	PAZ2812B1	20	40	179.0	170.10
Z=29	PAZ2912B1	20	40	184.0	176.20
Z=30	PAZ3012B1	20	40	191.0	182.30
Z=31	PAZ3112B1	20	40	196.0	188.30
Z=32	PAZ3212B1	20	40	204.0	194.40
Z=33	PAZ3312B1	20	40	209.0	200.40
Z=34	PAZ3412B1	20	40	215.0	206.50
Z=35	PAZ3512B1	20	40	221.0	212.50
Z=36	PAZ3612B1	20	40	227.0	218.60
Z=37	PAZ3712B1	20	40	233.0	224.60
Z=38	PAZ3812B1	20	40	239.0	230.70
Z=39	PAZ3912B1	20	40	245.0	236.70
Z=40	PAZ4012B1	20	40	252.0	242.80

\*Disponibile anche speciale a disegno e/o secondo normative ANSI/ASA. Disponibili nella versione semplice, doppia e tripla.

\*Available also special at design and/or in conformity with ANSI/ASA regulations. Available in single, doubles and triple version.

\*Disponibile aussi spécial au dessin et/ou selon normatives ANSI/ASA. Disponible la version simple, double et triple.