

ISO Nr.: 16B*

Passo / Pitch / Pas: 25,40 mm

Ø Rullo / Roller / Rouleau: 15.88 mm

Spessore pignone (mozzo escluso) / Sprocket thickness (hub excluded) /

Épaisseur du pignon (moyeu exclu): 16,2 mm

Dentature	Codice	Ø Foro (mm)	Spessore (mm) (mozzo incluso)	Ø esterno (mm)	Ø primitivo (mm)
Toothing	Code	Ø Hole (mm)	Thickness (mm) (hub included)	Ø external (mm)	Ø primitive (mm)
Dentures	Code	Ø Trou (mm)	Épaisseur (mm) (moyeu inclus)	Ø extérieur (mm)	Ø primitif (mm)
Z=10	PAZ1016B1	16	35	93.0	82.20
Z=11	PAZ1116B1	16	40	100.0	90.10
Z=12	PAZ1216B1	16	40	109.0	98.10
Z=13	PAZ1316B1	16	40	117.0	106.10
Z=14	PAZ1416B1	16	40	125.0	114.10
Z=15	PAZ1516B1	16	40	133.0	122.20
Z=16	PAZ1616B1	20	45	141.0	130.20
Z=17	PAZ1716B1	20	45	149.0	138.20
Z=18	PAZ1816B1	20	45	157.0	146.30
Z=19	PAZ1916B1	20	45	165.0	154.30
Z=20	PAZ2016B1	20	45	173.0	162.40
Z=21	PAZ2116B1	20	50	181.0	170.40
Z=22	PAZ2216B1	20	50	189.0	178.50
Z=23	PAZ2316B1	20	50	198.0	186.50
Z=24	PAZ2416B1	20	50	206.0	194.60
Z=25	PAZ2516B1	20	50	214.0	2.2070
Z=26	PAZ2616B1	20	50	222.0	210.70
Z=27	PAZ2716B1	20	50	230.0	218.80
Z=28	PAZ2816B1	20	50	238.0	226.80
Z=30	PAZ3016B1	20	50	254.0	243.00
Z=38	PAZ3816B1	25	50	321.0	307.60
Z=39	PAZ3916B1	25	50	329.0	315.60
Z=40	PAZ4016B1	25	50	337.0	323.70

*Disponibile anche speciale a disegno e/o secondo normative ANSI/ASA. Disponibili nella versione semplice, doppia e tripla.

*Available also special at design and/or in conformity with ANSI/ASA regulations. Available in single, doubles and triple version.

*Disponible aussi spécial au dessin et/ou selon normatives ANSI/ASA. Disponible la version simple, double et triple.