

ISO Nr.: 20B*

Passo / Pitch / Pas: 31.75 mm

Ø Rullo / Roller / Rouleau: 19.05 mm

Spessore pignone (mozzo escluso) / Sprocket thickness (hub excluded) /

Épaisseur du pignon (moyeu exclu): 18.5 mm

Dentature	Codice	Ø Foro (mm)	Spessore (mm) (mozzo incluso)	Ø esterno (mm)	Ø primitivo (mm)
Toothing	Code	Ø Hole (mm)	Thickness (mm) (hub included)	Ø external (mm)	Ø primitive (mm)
Dentures	Code	Ø Trou (mm)	Épaisseur (mm) (moyeu inclus)	Ø extérieur (mm)	Ø primitif (mm)
Z=10	PAZ1020B1	20	40	118.0	102.70
Z=11	PAZ1120B1	20	45	127.8	112.60
Z=12	PAZ1220B1	20	45	138.0	122.70
Z=13	PAZ1320B1	20	45	148.0	132.70
Z=14	PAZ1420B1	20	45	158.0	142.70
Z=15	PAZ1520B1	20	45	168.0	152.70
Z=16	PAZ1620B1	25	50	178.0	162.70
Z=17	PAZ1720B1	25	50	188.0	172.80
Z=18	PAZ1820B1	25	50	198.0	182.80
Z=19	PAZ1920B1	25	50	208.0	192.90
Z=20	PAZ2020B1	25	50	218.0	203.00
Z=21	PAZ2120B1	25	55	228.0	213.00
Z=22	PAZ2220B1	25	55	238.0	223.10
Z=23	PAZ2320B1	25	55	248.0	233.20
Z=24	PAZ2420B1	25	55	258.0	243.20
Z=25	PAZ2520B1	25	55	269.0	253.30

*Disponibile anche speciale a disegno e/o secondo normative ANSI/ASA. Disponibili nella versione semplice, doppia e tripla.

*Available also special at design and/or in conformity with ANSI/ASA regulations. Available in single, doubles and triple version.

*Disponible aussi spécial au dessin et/ou selon normatives ANSI/ASA. Disponible la version simple, double et triple.