

ISO Nr.: 24B*

Passo / Pitch / Pas: 38.10 mm

Ø Rullo / Roller / Rouleau: 25.40 mm

Spessore pignone (mozzo escluso) / Sprocket thickness (hub excluded) /

Épaisseur du pignon (moyeu exclu): 24.1 mm

Dentature	Codice	Ø Foro (mm)	Spessore (mm) (mozzo incluso)	Ø esterno (mm)	Ø primitivo (mm)
Toothing	Code	Ø Hole (mm)	Thickness (mm) (hub included)	Ø external (mm)	Ø primitive (mm)
Dentures	Code	Ø Trou (mm)	Épaisseur (mm) (moyeu inclus)	Ø extérieur (mm)	Ø primitif (mm)
Z=10	PAZ1024B1	20	45	138.0	123.29
Z=11	PAZ1124B1	25	50	150.0	135.20
Z=12	PAZ1224B1	25	50	162.0	147.20
Z=13	PAZ1324B1	25	50	174.0	159.20
Z=14	PAZ1424B1	25	50	186.0	171.20
Z=15	PAZ1524B1	25	50	199.0	183.30
Z=16	PAZ1624B1	25	55	211.0	195.30
Z=17	PAZ1724B1	25	55	222.0	207.30
Z=18	PAZ1824B1	25	55	234.0	219.40
Z=19	PAZ1924B1	25	55	247.0	231.50
Z=20	PAZ2024B1	25	55	259.0	243.50
Z=21	PAZ2124B1	25	60	271.0	255.60
Z=22	PAZ2224B1	25	60	283.0	267.70
Z=23	PAZ2324B1	25	60	295.0	279.80
Z=24	PAZ2424B1	25	60	307.0	291.90
Z=25	PAZ2524B1	25	60	320.0	304.00

*Disponibile anche speciale a disegno e/o secondo normative ANSI/ASA. Disponibili nella versione semplice, doppia e tripla.

*Available also special at design and/or in conformity with ANSI/ASA regulations. Available in single, doubles and triple version.

*Disponible aussi spécial au dessin et/ou selon normatives ANSI/ASA. Disponible la version simple, double et triple.